



# GLOBESTAR ENERGY FZE

*Energizing Globe*

## Test Report

**PRODUCT : BRIGHT STOCK 150**

| S.No | Characteristics                           | Test Method | Unit           | Result           |
|------|-------------------------------------------|-------------|----------------|------------------|
| 1    | Apperance                                 | Visual      | -              | Clear and Bright |
| 2    | Color                                     | ASTM D-1500 | -              | L 3.0            |
| 3    | Density at 15 <sup>0</sup> C              | ASTM D-1298 | Kg/l           | Report           |
| 4    | Kinematic Viscosity at 40 <sup>0</sup> C  | ASTM D-445  | cSt            | 503.5            |
| 5    | Kinematic Viscosity at 100 <sup>0</sup> C | ASTM D-445  | cSt            | 32.47            |
| 6    | Viscosity Index                           | ASTM D-2270 | -              | 96               |
| 7    | Flash Point                               | ASTM D-92   | <sup>0</sup> C | 304              |
| 8    | Pour Point                                | ASTM D-97   | <sup>0</sup> C | -6               |

\* Test methods shall be conducted in accordance with internationally accepted test methods such as ISO,ASTM or European Standrds.

**Globestar Energy FZE**

P.O Box: 42589, Phase 1, Hamriyah Free Zone,

Email: sales@globestarenergy.com

Web: www.globestarenergy.com

